

Operation and maintenance instructions of Weland hot-dip galvanized straight stairs/platforms

Weland's hot-dip galvanized straight staircases / platforms with steps in lattice grate / Letrist / WO2 and tear plate are virtually operation and maintenance free in terms of surface treatment.

In addition, reference is made to "Advice and guidance on hot dip galvanizing" (repair methods) published by the association of Danish hot dip galvanizers.

Weland straight stairs / platforms with stainless steel handrails can be followed by Industripolish, which cleans, polishes and gives a renewed shine to the surface, as well as leaving a smooth, corrosion-protective, dust- and dirt-repellent microfilm.

After approx. 1 year of use, it may be advisable to inspect and, if necessary, retighten bolt joints. Just as it may be recommended as needed to inspect and repair any damage marks, scratches on the surface or other rust stains with cold galvanizing material that can be purchased in a spray can. This material can, if desired, be finished with Alu-spray for the sake of appearance.

In exposed places, the WUC / UPE profile beams can be cleaned of leaves and dirt if necessary in the same way and time as when cleaning gutters. In addition, you are always welcome to contact us if you have questions about the maintenance of the purchased stair(s).

References

Advice and guidance on hot dip galvanizing

<http://nordicgalvanizers.com/wp-content/uploads/2020/01/Infoblade-reparation19-1.pdf>

Supplier Safety data sheets for Würth products

Würth Zinc / Aluspray Item number 0893111

<https://ehs.wuerth.com/ehs4customers/export/03184778.PDF>

Würth Zinc Spray Item number 0893114114

<https://ehs.wuerth.com/ehs4customers/export/03468868.PDF>

Würth Aluspray Item number 0893114115

<https://ehs.wuerth.com/ehs4customers/export/03456211.PDF>